



Резьба (дюйм) подключение папа	Модель	Доступность			Диаметр входного отв. (мм)	Диаметр вых. отв. (мм)	Расход (л/мин)														Угол распыления			Размеры					Нетто
		мин. заказ:30 шт.					0.2 bar	0.3 bar	0.4 bar	0.5 bar	0.7 bar	1 bar	1.5 bar	2 bar	3 bar	4 bar	6 bar	7 bar	0.7 bar	1.5 bar	4 bar	A	B	C	D	L	Вес		
		Нерж.сталь 304	Нерж. сталь 316	Нерж. сталь 316																		мм	мм	мм	мм	мм	кг		
1/2	3				11.1	7.9	7.3	9.0	10.3	11.6	13.7	16.3	20	23	28	33	40	43	62°	65°	67°	44.5	33.5	6.5	18.5	59	0.14		
	4	V	V	V	11.1	9.9	9.7	11.9	13.8	15.4	18.2	22	27	31	38	44	53	58	68°	71°	73°								
	5				11.1	11.9	12.2	14.9	17.2	19.3	23	27	33	39	47	54	67	72	74°	77°	80°								
	7				11.1	13.9	17.1	21	24	27	32	38	47	54	66	76	93	101	77°	80°	83°								
3/4	4				14.3	9.1	9.7	11.9	13.8	15.4	18.2	22	27	31	38	44	53	58	63°	66°	67°	51	42	8	24	69	0.21		
	5				14.3	10.7	12.2	14.9	17.2	19.3	23	27	33	39	47	54	67	72	67°	69°	70°								
	6	V	V	V	14.3	12.3	14.6	17.9	21	23	27	33	40	46	57	65	80	86	71°	73°	77°								
	7				14.3	13.9	17.1	21	24	27	32	38	47	54	66	76	93	101	73°	75°	80°								
	10				14.3	16.7	24	30	34	39	46	54	67	77	94	109	133	144	77°	80°	84°								