

# UMU J/I

## LARGE CAPACITY REELS



UMU ID40 B2HSB

UMU J/I reels, well engineered to hold a convenient length of flexible hose up to 40 meters (depending on the hose diameter), can be handled by a special design double recovery spring which ensures a proper and quick rewinding. They are recommended whenever long tunnels or machines must be cleaned from one single feed point.

Code	LP bar	E inch	U inch	DI mm	MF inch	LF m	W kg	DE mm	H mm	S mm	Swivel code
UMU JE30 B2LSB	20	1	1	20	3/4	30	40	530	550	520	-
UMU JF25 B2LSB				20	1	25					-
UMU ID25 B2HSB	200	1/2	1/2	10	1/2	25	26	530	550	370	XUM US30 B2
UMU IC40 B2HSB				10	3/8	40	36				-
UMU ID40 B2HSB				10	1/2	40	36	530	550	420	-

Abbreviations shown in the table are specified on page 33.

# XUM

## FLEXIBLE HOSES

To complete our range of reels, we supply the following set of flexible hoses, with different temperature and pressure operation ratings.

All hoses are made in food-grade NBR resistant to animal and vegetable greases and have a very smooth and glossy surface finish to avoid adhesion of dirt and pollutants.

*Please note that codes below refer to a 1 meter length*

### Example of order:

Being the selected reel the UMU JE30 B2LSB, the first one in the above table, required are 14 meters of a 3/4" hose designed to withstand a pressure of 20 bar.

Hose reel	UMU JE30 B2LSB	1 piece	
Reel 3/4 hose capacity		LF = 30 m	See above UMU J/I table
Max. working pressure	20 bar	Selected hose YXT RFEC E8	See table below
Order code	YXT RFEC E8	14 pieces	

Hose code for 1 m length	LP bar	LT °C	3/8 inch	1/2 inch	3/4 inch	1 inch
YXT RDCB E8 YXT RFCB E8 YXT RGCB E8	10	95		•	•	•
YXT RDEC E8 YXT RFEC E8 YXT RGEC E8	20	100		•	•	•
YXT RCKE E8 YXT RDKE E8	210 190	155	•	•		
YXT RCPE E8 YXT RDNE E8	400 350	155	•	•		